



PRODUCT SPECIFICATION

COBBLESTONE ENTRANCE MATTING

PRODUCT COMPOSITION

Manufacturing Process
Surface Aspect
Fiber

STANDARD / NORMS

ISO 2424
ISO 2424
CEE 83/623

DATA

Non woven
Hobnail (Berber) pattern
100% Solution dyed UV Stabilized
polypropylene
Premium composite rubber

Primary Backing

ISO 2424

PRODUCT DIMENSION

Pile Height (+ or - 0.5 mm)
Total Height (+ or - 7.5%)
Pile Weight (+ or - 7.5%)
Total Weight (+ or - 7.5%)
Width (+ or - 2%)
Custom

ISO 1765
ISO 1766
ISO 8543
ISO 8543
ISO 3018

.18 inch
.47 inch
44 oz/sy
65 oz/sy
6'7" or 13'2"
Special sizes, finished and logo mats

ELECTROSTATIC PROPERTIES

Dimensional Stability
Electrostatic Propensity
Electrical Resistivity
Sound Insulation
Thermal Retention

ASTM D7570-09
EN 1815
IBM / ICL
ISO 10140-1:2010
ISO 11092

Pass
>2kV
Pass, for R.H. > or = 40%
> or = 21dB
0.15 m K/W Pass

COLOR FASTNESS

To Light
To Water
To Shampoo
To Rubbing dry & wet

ISO 105 B02
ISO 105 E01
ISO 105 C06
ISO 105 X12

5
5
4 - 5
Dry 4 Wet 3 - 4

FLAMMABILITY RATING

Smoke Density
Surface Flammability

ASTM E662
FF 1-70 / ASTM D2859

Passes
Passes

LEED

MR Credit 4

LEED-NC v. 3 For 1 - 2 points: \$
value of all

12% recycled content

IEQ Credit 4.1

LEED-NC v. 3 For 1 point: low-
emitting adhesive with a VOC of 50
g/l or less for indoor releasable carpet
adhesive

Releasable VOC 0 g/l

IEQ Credit 4.3

LEED-NC v. 3 For 1 point: Low-
Emitting Materials- Flooring Systems

Green Label Plus certified

IEQ Credit 5

LEED-NC v. 3 For 1 point: semi-
permanently installed entrance
system at least 10' in length and
maintained on a weekly basis.

This carpet is a semi permanent
installation

