



## PRODUCT SPECIFICATION

### **BERBER TILE PLUS CARPET TILE**

#### **PRODUCT COMPOSITION**

Manufacturing Process  
Surface Aspect  
Fiber

#### **STANDARD / NORMS**

ISO 2424  
ISO 2424  
CEE 83/623

#### **DATA**

Non woven  
Hobnail (Berber) pattern  
100% Solution dyed UV Stabilized  
ASOTA™ polypropylene  
Premium (eco) Bitumen

Primary Backing

ISO 2424

#### **DIMENSION**

Pile Height ( + or - 0.5 mm)  
Total Height ( + or - 7.5%)  
Pile Weight ( + or - 7.5%)  
Total Weight ( + or - 7.5%)  
Tile Size ( + or - 2%)  
Packaging

ISO 1765  
ISO 1766  
ISO 8543  
ISO 8543  
ISO 3018

.375 inch  
.50 inch  
54 oz/sy  
169 oz/sy  
19.69 x 19.69

12 tiles per box or 32.5 sq.ft.

#### **ELECTROSTATIC PROPERTIES**

Dimensional Stability  
Electrostatic Propensity  
Electrical Resistivity  
Sound Insulation  
Thermal Retention

EN 986  
EN 1815  
IBM / ICL  
ISO 10140-1:2010  
ISO 11092

Pass  
>2kV  
Pass, for R.H. > or = 40%  
> or = 24dB  
0.13 m K/W Pass

#### **COLOR FASTNESS**

To Light  
To Water  
To Shampoo  
To Rubbing dry & wet

ISO 105 B02  
ISO 105 E01  
ISO 105 C06  
ISO 105 X12

5  
5  
5  
Dry 4 Wet 3 - 4

#### **FLAMMABILITY RATING**

Radiant Panel  
Smoke Density  
Surface Flammability

ASTM E648  
ASTM E662  
FF 1-70 / ASTM D2859

Class II  
Passes  
Passes

#### **LEED**

MR Credit 4

LEED-NC v. 3 For 1 - 2 points: \$ value of all

20% recycled content

IEQ Credit 4.1

LEED-NC v. 3 For 1 point: low-emitting adhesive with a VOC of 50 g/l or less for indoor releasable carpet adhesive

Releasable VOC 0 g/l

IEQ Credit 4.3

LEED-NC v. 3 For 1 point: Low-Emitting Materials- Flooring Systems

Green Label Plus certified

IEQ Credit 5

LEED-NC v. 3 For 1 point: semi-permanently installed entrance system at least 10' in length and maintained on a weekly basis.

This carpet is a semi permanent installation

