

# THE R.C. MUSSON RUBBER COMPANY



(330) 773-7651

(800) 321-2381

1320 E. ARCHWOOD AVE. – P.O. BOX 7038 – AKRON, OH 44306-0038

EMAIL – [info@mussonrubber.com](mailto:info@mussonrubber.com) – [www.mussonrubber.com](http://www.mussonrubber.com)

FAX (330) 773-3254

## PRODUCT SPECIFICATION

### COBBLESTONE PLUS

#### PRODUCT COMPOSITION

Manufacturing Process  
Surface Aspect  
Fiber

#### STANDARD / NORMS

ISO 2424  
ISO 2424  
CEE 83/623

#### DATA

Non woven  
Hobnail (Berber) pattern  
100% Solution dyed UV Stabilized  
ASOTA™ polypropylene  
Premium composite rubber

Primary Backing

ISO 2424

#### PRODUCT DIMENSION

Pile Height ( + or - 0.5 mm)  
Total Height ( + or - 7.5%)  
Pile Weight ( + or - 7.5%)  
Total Weight ( + or - 7.5%)  
Width ( + or - 2%)  
Custom

ISO 1765  
ISO 1766  
ISO 8543  
ISO 8543  
ISO 3018

.25 inch  
.47 inch  
54 oz/sy  
78 oz/sy  
6'7" or 13'2"  
Special sizes, finished and logo mats

#### ELECTROSTATIC PROPERTIES

Dimensional Stability  
Electrostatic Propensity  
Electrical Resistivity  
Sound Insulation  
Thermal Retention

ASTM D7570-09  
EN 1815  
IBM / ICL  
ISO 10140-1:2010  
ISO 11092

Pass  
>2kV  
Pass, for R.H. > or = 40%  
> or = 21dB  
0.15 m K/W Pass

#### COLOR FASTNESS

To Light  
To Water  
To Shampoo  
To Rubbing dry & wet

ISO 105 B02  
ISO 105 E01  
ISO 105 C06  
ISO 105 X12

5  
5  
4 - 5  
Dry 4 Wet 3 - 4

#### FLAMMABILITY RATING

Smoke Density  
Surface Flammability

ASTM E662  
FF 1-70 / ASTM D2859

Passes  
Passes

#### LEED

MR Credit 4

LEED-NC v. 3 For 1 - 2 points: \$ value of all

12% recycled content

IEQ Credit 4.1

LEED-NC v. 3 For 1 point: low-emitting adhesive with a VOC of 50 g/l or less for indoor releasable carpet adhesive

Releasable VOC 0 g/l

IEQ Credit 4.3

LEED-NC v. 3 For 1 point: Low-Emitting Materials- Flooring Systems

Green Label Plus certified

IEQ Credit 5

LEED-NC v. 3 For 1 point: semi-permanently installed entrance system at least 10' in length and maintained on a weekly basis.

This carpet is a semi permanent installation

