

THE R.C. MUSSON RUBBER COMPANY



(330) 773-7651

(800) 321-2381

1320 E. ARCHWOOD AVE. – P.O. BOX 7038 – AKRON, OH 44306-0038

EMAIL – info@mussonrubber.com – www.mussonrubber.com

FAX (330) 773-3254

PRODUCT SPECIFICATION

SPARTAN CARPET TILE

PRODUCT COMPOSITION

Manufacturing Process
Surface Aspect
Fiber

STANDARD / NORMS

ISO 2424
ISO 2424
CEE 83/623

DATA

Non woven
Flat Felt
100% solution dyed UV stabilized
ASOTA™ polypropylene fibers
Premium (eco) Bitumen

Primary Backing

ISO 2424

PRODUCT DIMENSION

Pile Height (+ or - 0.5 mm)
Total Height (+ or - 7.5%)
Pile Weight (+ or - 7.5%)
Total Weight (+ or - 7.5%)
Tile Size (+ or - 2%)
Packaging

ISO 1765
ISO 1766
ISO 8543
ISO 8543
ISO 3018

.18 inch
.26 inch
25 oz/sy
112 oz/sy
19.69 x 19.69
20 tiles per box or 6 square yards

ELECTROSTATIC PROPERTIES

Dimensional Stability
Electrostatic Propensity
Electrical Resistivity
Sound Insulation
Thermal Retention

EN 986
EN 1815
IBM / ICL
ISO 10140-1:2010
ISO 11092

Pass
>2kV
Pass, for R.H. > or = 40%
> or = 24dB
0.13 m K/W Pass

COLOR FASTNESS

To Light
To Water
To Shampoo
To Rubbing dry & wet

ISO 105 B02
ISO 105 E01
ISO 105 C06
ISO 105 X12

5
4 - 5
5
Dry 4 Wet 3 - 4

FLAMMABILITY RATING

Radiant Panel
Smoke Density
Surface Flammability

ASTM E648
ASTM E662
FF 1-70 / ASTM D2859

Class II
Passes
Passes

LEED

MR Credit 4

LEED-NC v. 3 For 1 - 2 points: \$ value of all

20% recycled content

IEQ Credit 4.1

LEED-NC v. 3 For 1 point: low-emitting adhesive with a VOC of 50 g/l or less for indoor releasable carpet adhesive

Releasable VOC 0 g/l

IEQ Credit 4.3

LEED-NC v. 3 For 1 point: Low-Emitting Materials- Flooring Systems

Green Label Plus certified

IEQ Credit 5

LEED-NC v. 3 For 1 point: semi-permanently installed entrance system at least 10' in length and maintained on a weekly basis.

This carpet is a semi permanent installation

