Cobblestone Entrance Mat Shop Drawings

Musson Cobblestone carpet matting is a wear-, fade-, and crush-resistant entrance matting that is excellent for high traffic areas. Available in 6'7" and 13'2" widths, this 4.1 ounce per square foot pile weight needlepunch polypropylene with a durable rubber crumb backing can be loose-laid or glued down. This 3/8" thick matting is resistant to mold, mildew, and stains and is available in full rolls of 82 foot long or in custom lengths. Vinyl beveled 2" nosing can be attached for surface mats.

Specifications – CB-CM

Furnish and install Musson CB-CM Cobblestone Entrance Matting of 100% polypropylene fiber needlepunch carpet. Carpet matting shall have a cobblestone pattern and be free from surface defects. Install 3/8" thick carpet matting, cut to size from standard width and lengths, in recess areas as indicated on drawing using recommended easy release adhesive (or on surface area using vinyl edging or aluminum beveled surface frame).

Quantity	Size	Color	Edging Attached (Y/N)	Special Notes

Mats are offered in:
Full rolls of 6'7" and 13'2" widths x 82' long
Cut lengths of 6'6" and 13'2" widths x any length up to 82'
Custom sizes up to 13'2" x 82'

APPROVED BY	DATE	TITLE