

Lock-N-Scrape Tile



Made from recyclable UV-resistant vinyl compound, Lock-N-Scrape has an enhanced drying & scraping system that is excellent for use in entryways and vestibules. A dimensionally stable tile that will not shrink or gap while effectively scraping dirt and other debris from foot traffic.

- Interlocking 50cm x 50cm tiles will allow versatility and customization for virtually any vestibule
- Ability to lock both carpeted and non-carpeted version in the same grid to offer better wiping/scraping
- Rugged vinyl capable of handling 600 lb. rolling loads
- Dirt and other debris fall through the openings

Specifications

Lock-N-Scrape with Carpet

Construction: TPE/PVC with Nylon Carpet

Total Height: 0.47"

Total Weight: 3.0 lbs

Insert Carpet: 8.70" x 1.38"

Tile Size: 19.69" x 19.69"

Tiles (19.69" x 19.69" ea): 12 tiles per box (32.5 sq. ft.)

Lock-N-Scrape without Carpet

Construction: 100% TPE

Total Height: 0.47"

Total Weight: 2.5 lbs

Tile Size: 19.69" x 19.69"

Tiles (19.69" x 19.69" ea): 20 tiles per box (54.18 sq. ft.)



Technical Specifications

Friction (ASTM D-2047-96)

Wet .60

Standard Rolling Load

600lbs/wheel

Fire Resistance (ASTM E648)

Class 1

UV Resistance

Utilizes recyclable, UV resistant PVC/NBR