Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 07/20/2023

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture Product Name: EXCELSIOR EN-610 A

Intended Use of the Product

Use of the Substance/Mixture: No use is specified.

Name, Address, and Telephone of the Responsible Party

Company

The RC Musson Rubber Co 1320 E Archwood Ave Akron, OH 44306 1-800-321-2381

Manufacturer

Helmitin Inc. 11110 Airport Road Olive Branch, MS 38654 Phone: 877.823.2624

www.helmitin.com

Emergency Telephone Number

Emergency number: CHEMTREC 1-800-424-9300 / CANUTEC 613-996-6666

Classification of the Substance or Mixture

Classification (GHS-US)Skin Irrit. 2H315Eye Irrit. 2AH319Skin Sens. 1H317Aquatic Chronic 2H411Full text of H-phrases: see section 16

Label Elements

GHS-US Labeling Hazard Pictograms (GHS-US)



Signal Word (GHS-US)	: Warning
Hazard Statements (GHS-US)	: H315 - Causes skin irritation.
	H317 - May cause an allergic skin reaction.
	H319 - Causes serious eye irritation.
	H411 - Toxic to aquatic life with long lasting effects.
Precautionary Statements (GHS-US)	: P261 - Avoid breathing vapors, mist, or spray.
	P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves, protective clothing, and eye protection.
	P302+P352 - IF ON SKIN: Wash with plenty of water.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.

Version: 1.2

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Flammable vapors can accumulate in head space of closed systems.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixture</u>		
Name	Product Identifier	% (w/w)
Bisphenol A-epichlorohydrin polymer	(CAS No) 25068-38-6	10 - 30
Trimethylolpropane triacrylate	(CAS No) 15625-89-5	10 - 30
Quartz*	(CAS No) 14808-60-7	0.1 - 1.0

*This product contains a material that may be hazardous when present as an airborne dust. Since this product is in a liquid form, the material is not able to become airborne and cannot be inhaled. Thus, the hazards usually associated with this material are not applicable to this product.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Obtain medical attention if irritation persists.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes eye irritation. Causes skin irritation. May cause an allergic skin reaction.

Inhalation: May cause respiratory irritation.

Skin Contact: Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

Eye Contact: Causes serious eye damage. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

Ingestion: Not available

Chronic Symptoms: None expected.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Potentially violent decomposition can occur above 350 °C.

Explosion Hazard: Product is not explosive but if hazardous polymerization occurs can have an oxidizing effect that could lead to fire and possible explosion.

Reactivity: Hazardous reactions may occur on contact with certain chemicals. Refer to incompatible materials.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Hazardous Combustion Products: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing vapor, mist, or spray. Use only outdoors or in a well-ventilated area.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods,

protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. **Environmental Precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Use only nonsparking tools.

Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: The substance will polymerize due to heating, on contact with peroxides, and under the influence of light. Heating may cause violent combustion or explosion producing acrid smoke. The substance may also spontaneously polymerize if it is not stabilized. Product to be handled in a closed system and under strictly controlled conditions. Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Amines. Fluorine. Ammonium salts.

Specific End Use(s)

No use is specified.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL (STEL) (mg/m ³)	250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Alberta	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate)
British Columbia	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable)
Manitoba	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m³)	0.1 mg/m ³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable fraction)
Nunavut	OEL TWA (mg/m³)	0.1 mg/m ³ (respirable mass)
Northwest Territories	OEL TWA (mg/m³)	0.1 mg/m ³ (respirable mass)
Ontario	OEL TWA (mg/m³)	0.10 mg/m ³ (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable fraction)
Québec	VEMP (mg/m ³)	0.1 mg/m ³ (respirable dust)
Saskatchewan	OEL TWA (mg/m³)	0.05 mg/m ³ (respirable fraction)
Yukon	OEL TWA (mg/m³)	300 particle/mL

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure, but are not required. Product to be handled under strictly controlled conditions. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. **Environmental Exposure Controls:** Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Paste – Viscous Liquid
Appearance	: Beige Thick Liquid
Odor	: Not available
Odor Threshold	: Not available
рН	: Not available
Evaporation Rate	: Not applicable
Melting Point	: 32°F
Freezing Point	: 32° F
Boiling Point	: > 392 °F (200 °C)
Flash Point	: > 200 °F (93 °C) (Setaflash method)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Specific Gravity	:	1.4
Solubility	:	Not available
Partition Coefficient: N-Octanol/Water	:	Not available
Viscosity	:	Approximately 72,000 cps
Explosion Data – Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	:	Not expected to present an explosion hazard due to static discharge.
VOC Content	:	<12 g/L (<0.1 lbs/gal)

5

SECTION 10: STABILITY AND REACTIVITY				
	artain chemicals. Refer to incompatible materials			
<u>Reactivity</u>: Hazardous reactions may occur on contact with certain chemicals. Refer to incompatible materials. <u>Chemical Stability</u> : Stable under recommended handling and storage conditions (see section 7).				
	on may occur upon contact with heat or imcompatible materials.			
Conditions to Avoid: Direct sunlight. Extremely high or low te				
Incompatible Materials: Strong acids, strong bases, strong ox				
	his material may produce hazardous carbon dioxide (CO ₂), carbon			
monoxide (CO), various low molecular weight hydrocarbons, an				
SECTION 11: TOXICOLOGICAL INFORMATION				
Information on Toxicological Effects - Product				
Acute Toxicity: Not classified				
LD50 and LC50 Data: Not available				
Skin Corrosion/Irritation: Causes skin irritation.				
Serious Eye Damage/Irritation: Causes serious eye irritation.				
Respiratory or Skin Sensitization: May cause an allergic skin rea	action.			
Germ Cell Mutagenicity: Not classified				
Teratogenicity: Not classified				
Carcinogenicity: Not classified				
Specific Target Organ Toxicity (Repeated Exposure): Not classif	fied			
Reproductive Toxicity: Not classified				
Specific Target Organ Toxicity (Single Exposure): Not classified				
Aspiration Hazard: Not classified				
Symptoms/Injuries After Inhalation: May cause respiratory irritation.				
Symptoms/Injuries After Skin Contact: Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning,				
dryness, and dermatitis. May cause an allergic skin reaction.	age. Symptoms may include: Redness, pain, swelling, itching, burning,			
tearing, and blurred vision.	age. Symptoms may metude. Neuress, pain, sweining, terning, burning,			
Chronic Symptoms: None expected.				
Information on Toxicological Effects - Ingredient(s)				
LD50 and LC50 Data:				
Bisphenol A-epichlorohydrin polymer (25068-38-6)				
LD50 Oral Rat	> 2000 mg/kg			
LD50 Dermal Rat	> 2000 mg/kg			
Trimethylolpropane triacrylate (15625-89-5)				
LD50 Dermal Rabbit 5000 mg/kg				
Quartz (14808-60-7)				
LD50 Oral Rat > 5000 mg/kg				
LD50 Dermal Rat > 5000 mg/kg				
Quartz (14808-60-7)				
IARC Group				
National Toxicology Program (NTP) Status	Known Human Carcinogens.			

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 12: ECOLOGICAL INFORMATION

<u>Toxicity</u>

Ecology - General: Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Bisphenol A-epichlorohydrin polymer (25068-38-6)			
LOEC (acute) 1 mg/l Daphnia magna			
NOEC chronic crustacea	0.3 mg/l Daphnia magna		

Persistence and Degradability Not available

Bioaccumulative Potential

Mobility in Soil Not available

Other Adverse Effects Not available

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: This material is hazardous to the aquatic environment. Keep out of sewers and waterways. Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

SECTION 14. INANSPORT	INFORMATION
In Accordance with DOT	Not regulated for transport
In Accordance with IMDG	
Proper Shipping Name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin)
Hazard Class	: 9
Identification Number	: UN3082
Packing Group	: 111
Label Codes	: 9
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Marine pollutant	: Marine pollutant
In Accordance with IATA	
Proper Shipping Name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin)
Packing Group	: 111
Identification Number	: UN3082
	: 9
Hazard Class	9
Label Codes	: 9
ERG Code (IATA)	: 9L

In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Delayed (chronic) health hazard Bisphenol A-epichlorohydrin polymer (25068-38-6) Immediate (acute) health hazard Listed on the United States TSCA (Toxic Substances Control Act) inventory Quartz (14808-60-7) Listed on the United States TSCA (Toxic Substances Control Act) inventory Trimethylolpropane triacrylate (15625-89-5) Listed on the United States TSCA (Toxic Substances Control Act) inventory Trimethylolpropane triacrylate (15625-89-5)

US State Regulations

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Proposition 65 – WARNING: Cancer - www.P65Warnings.ca.gov.

Quartz (14808-60-7)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Canadian Regulations

Bisphenol A-epichlorohydrin polymer (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List)

Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

Trimethylolpropane triacrylate (15625-89-5)

Listed on the Canadian DSL (Domestic Substances List)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date

: 07/20/2023

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H319	Causes serious eye irritation	
H411 Toxic to aquatic life with long lasting effects		

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. North America GHS US 2012 & WHMIS 2015